

# Product information sheet for separate control gear in/with **Audrey Pendant**

**Supplier name:** UIMAGE ApS

**Supplier address:** Havnegade 29, 1058 Copenhagen Denmark

**Model identifier:** HLV1230LD (from batch 2)

Input parameters	AC 220-240V, 50/60Hz, 170mA
Output parameters	DC 12V, 2,5A Max
Dimming compatible:	Yes
Compatible dimming control system(s):	Trailing- or Leading-edge (TRIAC)
Require external dimmer?	Yes
Recommended external dimmers:	Please see recommended external dimmers list in separate document
Maximum output power of the control gear:	30 W
Type of light-source for which this control gear is intended for:	LED
Efficiency in full-load:	82,6 %
No-load power:	0 W
Standby power:	0 W
Network standby power:	N/A
Warning:	This control gear must not be used with other products than, the product it came pre-installed with
Outer dimensions:	Height = 29,5 mm
	Width = 46 mm
	Depth = 159 mm
Weight:	164 g

**Supplier name:** UIMAGE ApS

**Supplier address:** Havnegade 29, 1058 Copenhagen Denmark

**Model identifier:** SLD30-12VL-E (only batch 1)

Input parameters	AC 220-240V, 50/60Hz, 180mA
Output parameters	DC 12V, 2,5A Max
Dimming compatible:	Yes
Compatible dimming control system(s):	Trailing- or Leading-edge (TRIAC)
Require external dimmer?	Yes
Recommended external dimmers:	Please see recommended external dimmers list in separate document
Maximum output power of the control gear:	30 W
Type of light-source for which this control gear is intended for:	LED
Efficiency in full-load:	82,7 %
No-load power:	0 W
Standby power:	0 W
Network standby power:	N/A
Warning:	This control gear must not be used with other products than, the product it came pre-installed with
Outer dimensions:	Height = 22 mm
	Width = 50 mm
	Depth = 145,5 mm
Weight:	187 g