

PH 5-4½ & PH 6½-6

White, 5741085868, Designed by Poul Henningsen

Type:	
Product:	
Project:	
Modified:	



Technical specifications

Materials

Shades and anti-glare disc: Spun aluminium.

Spacers: Rolled aluminium.

Finishes

White.

Mounting

PH 5-4½ (E27):

3 m. Cord.

Canopy included.

PH 5-4½ (LED):

4 m. Cord.

LED canopy with driver included.

PH 6½-6 (LED):

4 m. Cord and wire.

LED canopy or external driver box with driver included.

Information

PH 5-4½: LED Upgrade kit fits as standard PH 5-4½ E27 produced after 1983. PH 6½-6: The LED insert fits as standard PH 6½-6 E27/E40 produced after 1999. For PH 6½-6 produced prior to 1999 you need a renovation kit which can be acquired as an accessory. Please note the LED insert does not fit variants produced with metal halide. For LED replacement kits please do contact Louis Poulsen.

For the E-socket product variants, bulbs are not included. LED light source is part of the product.

PH 5-4½ & PH 6½-6

White, 5741085868, Designed by Poul Henningsen

Maximum distance between external driver box and fixture:
20 m. For mounting instructions, see download section on the
product detail page.

Variant Options

For particular variant options, please check our online Product Variants Configurator on the
product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FREQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (CM) / W (KG)
5741085868	1x70W E27		791	-	White textile cord	WHT, 016	466 / 318 / 466 cm / 5.6 kg
5741094985	LED 2700K 96W		4686	Wireless bluetooth	White textile cord and wire	WHT, 016	650 / 500 / 650 cm / 18.1 kg
5741101687	LED 3000-1800K D2W 41W		1446	Phase dimming (mains dimm)	White textile cord	WHT, 016	466 / 318 / 466 cm / 7.9 kg
5741101700	LED 3000-1800K D2W 41W		1446	Wireless bluetooth	White textile cord	WHT, 016	466 / 318 / 466 cm / 7.9 kg
5741921210				-	White textile cord	WHT, 016	- / - / - cm / 2.5 kg